现货库存、技术资料、百科信息、热点资讯，精彩尽在鼎好！

SPP2301
P-Channel Enhancement Mode MOSFET

DESCRIPTION

The SPP2301 is the P-Channel logic enhancement mode power field effect transistors are produced using high cell density , DMOS trench technology.

This high density process is especially tailored to minimize on-state resistance.

These devices are particularly suited for low voltage application such as cellular phone and notebook computer power management and other battery powered circuits, and low in-line power loss are needed in a very small outline surface mount package.

APPLICATIONS

- Power Management in Note book
- Portable Equipment
- Battery Powered System
- DC/DC Converter
- Load Switch
- DSC
- LCD Display inverter

FEATURES

- -20V/-2.8A,$R_{DS(ON)}$=120mΩ@V_{GS}=-4.5V
- -20V/-2.0A,$R_{DS(ON)}$=170mΩ@V_{GS}=-2.5V
- Super high density cell design for extremely low $R_{DS\ (ON)}$
- Exceptional on-resistance and maximum DC current capability
- SOT-23-3L package design

PIN CONFIGURATION(SOT-23-3L)



PART MARKING



Y : Year Code
W : Week Code

SPP2301
P-Channel Enhancement Mode MOSFET

PIN DESCRIPTION

Pin	Symbol	Description
1	G	Gate
2	S	Source
3	D	Drain

ORDERING INFORMATION

Part Number	Package	Part Marking
SPP2301S23RG	SOT-23-3L	01YW

※ Week Code : A ~ Z(1 ~ 26) ; a ~ z(27 ~ 52)
※ SPP2301S23RG : Tape Reel ; Pb – Free

ABSOULTE MAXIMUM RATINGS

(T_A=25℃ Unless otherwise noted)

Parameter		Symbol	Typical	Unit
Drain-Source Voltage		V_{DSS}	-20	V
Gate –Source Voltage		V_{GSS}	±12	V
Continuous Drain Current(T_J=150℃)	T_A=25℃	I_D	-3.0	A
	T_A=70℃		-2.0	
Pulsed Drain Current		I_{DM}	-10	A
Continuous Source Current(Diode Conduction)		I_S	-1.6	A
Power Dissipation	T_A=25℃	P_D	1.25	W
	T_A=70℃		0.8	
Operating Junction Temperature		T_J	150	℃
Storage Temperature Range		T_{STG}	-55/150	℃
Thermal Resistance-Junction to Ambient		$R_{\theta JA}$	120	℃/W

SPP2301
P-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS

(T_A=25℃ Unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS}=0V,I_D=-250uA	-20			V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=-250uA	-0.45		-1.5	
Gate Leakage Current	I_{GSS}	V_{DS}=0V,V_{GS}=±12V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-20V,V_{GS}=0V			-1	uA
		V_{DS}=-20V,V_{GS}=0V T_J=55℃			-10	
On-State Drain Current	$I_{D(on)}$	V_{DS}≦-5V,V_{GS}=-4.5V	-6			A
		V_{DS}≦-5V,V_{GS}=-2.5V	-3			
Drain-Source On-Resistance	$R_{DS(on)}$	V_{GS}=-4.5V,I_D=-2.8A		0.095	0.12	Ω
		V_{GS}=-2.5V,I_D=-2.0A		0.150	0.17	
Forward Transconductance	gfs	V_{DS}=-5V,I_D=-2.8A		6.5		S
Diode Forward Voltage	V_{SD}	I_S=-1.6A,V_{GS}=0V		-0.8	-1.2	V
Dynamic						
Total Gate Charge	Q_g	V_{DS}=-6V,V_{GS}=-4.5V I_D≡-2.8A		5.8	10	nC
Gate-Source Charge	Q_{gs}			0.85		
Gate-Drain Charge	Q_{gd}			1.7		
Input Capacitance	C_{iss}	V_{DS}=-6V,V_{GS}=0V f=1MHz		415		pF
Output Capacitance	C_{oss}			223		
Reverse Transfer Capacitance	C_{rss}			87		
Turn-On Time	$t_{d(on)}$	V_{DD}=-6V,R_L=6Ω I_D≡-1.0A,V_{GEN}=-4.5V R_G=6Ω		13	25	ns
	t_r			36	60	
Turn-Off Time	$t_{d(off)}$			42	70	
	t_f			34	60	

SPP2301
P-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS









TYPICAL CHARACTERISTICS









TYPICAL CHARACTERISTICS







SOT-23-3L PACKAGE OUTLINE



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.400	0.012	0.016
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.700REF		0.028REF	
L1	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

©The SYNC Power logo is a registered trademark of SYNC Power Corporation
©2004 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved
SYNC Power Corporation
9F-5, No.3-2, Park Street
NanKang District (NKSP), Taipei, Taiwan, 115, R.O.C
Phone: 886-2-2655-8178
Fax: 886-2-2655-8468
©http://www.syncpower.com